

1	2	3	4	5	6	7	8	9																																																																					
<table><tr><td colspan="2">Main Specification</td></tr><tr><td>Sensor</td><td>1/2.49"</td><td>1/2.8"</td></tr><tr><td>Max image</td><td>φ7.2</td><td>φ7.0</td></tr><tr><td>Resolution</td><td>11.3M</td><td>8.29M</td></tr><tr><td>CRA</td><td><10.8°</td><td><10°</td></tr><tr><td rowspan="3">FOV(°)</td><td>D</td><td>54°±3°(7.250mm)</td><td>48.3°±3°(6.388mm)</td></tr><tr><td>H</td><td>47.9°±3°(6.335mm)</td><td>42.6°±3°(5.568mm)</td></tr><tr><td>V</td><td>27.6°±3°(3.527mm)</td><td>24.6°±3°(3.132mm)</td></tr><tr><td>FFL(IR 0.3+(G0.5)</td><td>4.72±0.2</td><td>4.79±0.2</td></tr><tr><td>BFL(IR 0.3+(G0.5)</td><td>7.37±0.2</td><td>7.44±0.2</td></tr><tr><td>ITL(IR 0.3+(G0.5)</td><td>22.94±0.2</td><td>23.01±0.2</td></tr><tr><td>Relative illumination</td><td>>50%</td><td>>65%</td></tr><tr><td>Optical Distortion</td><td><-12%</td><td><-1%</td></tr><tr><td>EFL</td><td colspan="2">7.2±5%</td></tr><tr><td>F.No</td><td colspan="2">2.2±5%</td></tr><tr><td>Thread</td><td colspan="2">M12×P0.5</td></tr><tr><td>Barrel Material</td><td colspan="2">LY6061(black)</td></tr><tr><td>Water-Proof grade</td><td colspan="2">none</td></tr><tr><td>Axis</td><td colspan="2">1700 TV line</td></tr><tr><td>0.7</td><td colspan="2">1200 TV line</td></tr><tr><td colspan="3">SURFACE QUALITY</td></tr><tr><td>Center</td><td colspan="2">60-40</td></tr><tr><td>Margin</td><td colspan="2">60-40</td></tr></table>									Main Specification		Sensor	1/2.49"	1/2.8"	Max image	φ7.2	φ7.0	Resolution	11.3M	8.29M	CRA	<10.8°	<10°	FOV(°)	D	54°±3°(7.250mm)	48.3°±3°(6.388mm)	H	47.9°±3°(6.335mm)	42.6°±3°(5.568mm)	V	27.6°±3°(3.527mm)	24.6°±3°(3.132mm)	FFL(IR 0.3+(G0.5)	4.72±0.2	4.79±0.2	BFL(IR 0.3+(G0.5)	7.37±0.2	7.44±0.2	ITL(IR 0.3+(G0.5)	22.94±0.2	23.01±0.2	Relative illumination	>50%	>65%	Optical Distortion	<-12%	<-1%	EFL	7.2±5%		F.No	2.2±5%		Thread	M12×P0.5		Barrel Material	LY6061(black)		Water-Proof grade	none		Axis	1700 TV line		0.7	1200 TV line		SURFACE QUALITY			Center	60-40		Margin	60-40	
Main Specification																																																																													
Sensor	1/2.49"	1/2.8"																																																																											
Max image	φ7.2	φ7.0																																																																											
Resolution	11.3M	8.29M																																																																											
CRA	<10.8°	<10°																																																																											
FOV(°)	D	54°±3°(7.250mm)	48.3°±3°(6.388mm)																																																																										
	H	47.9°±3°(6.335mm)	42.6°±3°(5.568mm)																																																																										
	V	27.6°±3°(3.527mm)	24.6°±3°(3.132mm)																																																																										
FFL(IR 0.3+(G0.5)	4.72±0.2	4.79±0.2																																																																											
BFL(IR 0.3+(G0.5)	7.37±0.2	7.44±0.2																																																																											
ITL(IR 0.3+(G0.5)	22.94±0.2	23.01±0.2																																																																											
Relative illumination	>50%	>65%																																																																											
Optical Distortion	<-12%	<-1%																																																																											
EFL	7.2±5%																																																																												
F.No	2.2±5%																																																																												
Thread	M12×P0.5																																																																												
Barrel Material	LY6061(black)																																																																												
Water-Proof grade	none																																																																												
Axis	1700 TV line																																																																												
0.7	1200 TV line																																																																												
SURFACE QUALITY																																																																													
Center	60-40																																																																												
Margin	60-40																																																																												
<table><tr><td colspan="2">TOLERANCE: +0.05</td></tr><tr><td colspan="2">ANGULAR TOLERANCES ARE±30°</td></tr><tr><td colspan="2">DRAFT ANGLES AREA±0.5°/SIDE</td></tr><tr><td>三角法</td><td>材料(环保)</td></tr><tr><td>名称</td><td>单位</td></tr><tr><td>代号</td><td>比例</td></tr><tr><td>CY0807A-M05规格书</td><td>2:1</td></tr><tr><td>CY0807A-M05-SPEC</td><td>1/1</td></tr><tr><td>版本</td><td>版本</td></tr><tr><td>V02</td><td>V02</td></tr></table>									TOLERANCE: +0.05		ANGULAR TOLERANCES ARE±30°		DRAFT ANGLES AREA±0.5°/SIDE		三角法	材料(环保)	名称	单位	代号	比例	CY0807A-M05规格书	2:1	CY0807A-M05-SPEC	1/1	版本	版本	V02	V02																																																	
TOLERANCE: +0.05																																																																													
ANGULAR TOLERANCES ARE±30°																																																																													
DRAFT ANGLES AREA±0.5°/SIDE																																																																													
三角法	材料(环保)																																																																												
名称	单位																																																																												
代号	比例																																																																												
CY0807A-M05规格书	2:1																																																																												
CY0807A-M05-SPEC	1/1																																																																												
版本	版本																																																																												
V02	V02																																																																												

Technical drawing of the camera module showing front and top views with dimensions.

Front View Dimensions:

- Total length: 23.01±0.2(TTL)
- Distance from top to sensor: 17.43
- Distance from sensor to bottom: 4.3
- Distance from bottom to base: 13.7
- Distance from base to bottom: 7.44±0.2
- Distance from bottom to base: 4.79±0.2
- Distance from base to bottom: 5.4
- Distance from bottom to base: 14.0
- Distance from bottom to base: 14.0

Top View Dimensions:

- Total width: 34.253
- Distance from left to right: 31.759
- Distance from left to right: 2-φ1.45
- Distance from left to right: 2-φ1.9

Other labels: IR, Image, Cover glass, C2