

1		2		3		4		5		6		7		8		9	
A	<div>24±0.2(TTL)</div>																
	<div>Φ18.8⁰_{-0.1}</div>																
	<div>7.67</div>																
	<div>21.53±0.03</div>																
	<div>1.94±0.02</div>																
	<div>5.85±0.02</div>																
	<div>M12×P0.5-6g</div>																
	<div>IR Image Cover glass</div>																
	<div>24±0.2(TTL)</div>																
	Main Specification																
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	
<div>5.85±0.02</div>																	
<div>M12×P0.5-6g</div>																	
<div>IR Image Cover glass</div>																	
<div>24±0.2(TTL)</div>																	
Main Specification																	
Sensor		IMX415 (3840X2160X1.45um)															
Max image		φ8															
F.No		2.8±5%															
EEL		3.37±5%															
FOV(°)		1MHx2(lmm)															
D		86.5°±5°															
H		78.4°±5°															
V		49.4°±5°															
FFL(lR (t=0.3)in+Cover glass(t=0.5)in)		1.94±0.2															
BFL(lR (t=0.3)in+Cover glass(t=0.5)in)		5.85±0.2															
TTL		24±0.2															
Relative illumination		78%															
TV Distortion		<1%(D)															
Structure		5G+2G(ASP)															
Resolution		8.29M															
CRA		9°															
Resolution																	
Axis		≥0.4@250lp/mm															
0.7γ		T		≥0.3@250lp/mm													
		S		≥0.3@250lp/mm													
SURFACE QUALITY																	
Center		60-40															
Margin		60-40															
1		2		3		4		5		6		7		8		9	
<div>24±0.2(TTL)</div>																	
<div>Φ18.8⁰_{-0.1}</div>																	
<div>7.67</div>																	
<div>21.53±0.03</div>																	
<div>1.94±0.02</div>																	